



# VENUS MEJANO

Top of the range masonry bridge saw for a perfect cutting and mitering on any kind of construction material.  
 Exclusive teeth-belt / wheel transmission system for a precise and comfortable cut on large slabs.  
 It is provided with a self-cleaning system by felts for the bearings rolling tracks.  
 Foldable blade guard and cutting depth adjustment standard in all versions.  
 Max. blade capacity of 300 mm and 350 mm diameter.  
 60% of the components manufactured of stainless materials.



**VENUS 85**

**VENUS 125**

**VENUS 150**



Exclusive teeth-belt / wheel transmission system.



Self-cleaning felts for the bearings rolling tracks at the aluminium bridge.



Foldable blade guard to maximize cutting depth.



Specifications	VENUS <i>Single phase</i>	VENUS <i>Three phase</i>
Motor power (Kw)	2,2	3
Motor voltage (V)	230	230 / 400
Motor frequency (Hz)		50 & 60
Water basin capacity (L)		45
Blade bore diameter (mm)		25,4

	VENUS 85	VENUS 125	VENUS 150
Dimensions (LxWxH) (mm)	1499 x 765 x 1234	1892 x 765 x 1234	2193 x 765 x 1234
Net Weight (Kg)	84	102,7	112,7
Max. cutting length (mm)	850	1250	1550
Blade diameter (mm)		Ø300 & Ø350	
Max. cutting depth (mm)		With blade Ø300 : 70 With blade Ø350 : 100	
Mitring cut		Yes	
Motor R.P.M.		2.800	

\* All models available with Three phase or Single phase motor versions.

